



Integra® ANSI • CE • CSA •



Adjustable temples ensure reliable performance // Custom imprinting available

Black Frame | 5 Variations

- SB410S ●●● Clear
- SB410ST ●●● Clear AF
- SB420S ●●● Gray
- SB450SF ●●● 5.0 IR Filter
- SB460SF ●●● 3.0 IR Filter



SM4



SN4



SNWR4



SR4

Mixed Blue Frame | 1 Variation

- SM410S ●●● Clear

Red, White & Blue Frame | 1 Variation

- SNWR410S ●●● Clear

Black Ratchet Frame | 1 Variation

- SB410SR ●●● Clear

Blue Frame | 1 Variation

- SN410S ●●● Clear

Red Frame | 1 Variation

- SR410S ●●● Clear

Part No.	Lens Marking	Temple Marking
SB410S	P + U6	P Z87 + / P c SEI Z94.3
SB410ST	P + U6	P Z87 + / P c SEI Z94.3
SB420S	P + U6 L3	P Z87 + / P c SEI Z94.3
SB450SF	P + 5.0	P Z87 +
SB460SF	P + 3.0	P Z87 +
SB410SR	P + U6	P Z87 +
SM410S	P + U6	P Z87 + / P c SEI Z94.3
SN410S	P + U6	P Z87 + / P c SEI Z94.3
SNWR410S	P + U6	P Z87 + / P c SEI Z94.3
SR410S	P + U6	P Z87 + / P c SEI Z94.3

General Specifications

Weight: 35 gm
 PD: 68 mm
 Lens base: 4 curve
 Lens size diagonal: 138 mm
 Lens size vertical: 39 mm
 Lens thickness: 2.0 mm
 Overall length (lens - tip): 85 mm
 Overall width (hinge - hinge): 149 mm

Materials

Lens: polycarbonate
 Side shield: polycarbonate
 Frame: nylon 66
 Temples: nylon 66
 Hinge: polycarbonate
 Screw: nickel plated
 Nosepiece: polycarbonate

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 3.0: IR3 lens
 5.0: IR5 lens

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L3: 18% Max. Visible Light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices